

Glazerite UK Group Ltd are a leading national trade fabricator of UPVC windows and doors including VEKA, Halo, Deceuninck and Residence.

Now a trusted supply partner of the ALUK range of windows.



39-43 Rixon Court Finedon Rd Industrial Estate Wellingborough Northamptonshire NN8 4BA

Tel: (01933) 443222 Fax: (01933) 443244 Email: sales@glazerite.net





OPTIO 58BW HI FLUSH WINDOW CONTENT

Combining minimal sight lines with maximum durability & weather resistance.

Perfect for a range of new build or refurbishment projects, the 58BW flush window offers a sleek flush finish and advanced functionality. With a choice of window configurations and slim sashes, the 58BW can achieve stunning aesthetics without compromising on the exceptional standards of weather protection, security and durability.

DESIGN FEATURES

- Certified under the Secured By Design scheme
- Tested to PAS 24
- Features integrated deep head profiles for ease of trickle ventilation
- A polyamide thermal break design to improve thermal performance

OPTIONS


- Glazing 24mm 40mm
- Internally or externally glazed
- Available in a selection of single or dual colours, as well as anodised finishes
- Available in flush, bay, chamfered, heritage, ovolo and contemporary aesthetics
- 70mm frame depth
- Available in a range of configurations: top hung, bottom hung, side hung, fixed light, multi-light and French casement






Tall











Top Hung & Fixed Lights






Side Hung




French Casement





Side Hung & Fixed Lights




SPECIFICATIONS


PERFORMANCE AND ACCREDITATION

U-Value (Double Glazing) (Ug: 1.0 W/m2K)	1.4 W/m ² K
Air Permeability	Class 4 (600 Pa)
Water Tightness	Class 9a (600 Pa)
Wind Resistance	Class E2400 (2400 Pa)
Acoustic Performance	Rw (C;Ctr) 42 (-1;-5) dB
Security	PAS 24 & SBD
3rd Party Certification Q-Mark	\checkmark
0)/07EN	
SYSTEM	
SYSTEM Depth	70mm
	70mm
Depth	70mm
Depth CONFIGURATIONS	70mm
Depth CONFIGURATIONS Top Hung	70mm ✓ ✓ ✓
Depth CONFIGURATIONS Top Hung Side Hung	70mm

Jamb Section



58BW HI Flush Head



*Specifications show what can be achieved with the system but not all products will meet them automatically (depending on size, configuration, e.t.c.). Any specific requirements should be discussed with the technical team before ordering. The specifications on this page are subject to change without warning.

SIZE AND WEIGHT LIN	AITS
Top Hung	
Max. size (mm)	1400w x 1200h
Min. size (mm)	350w x 250h
Max. Weight	35kg
Side Hung	
Max. size (mm)	700w x 1400h
Min. size (mm)	300w x 350h
Max. Weight	26kg
Bottom Hung	
Max. Weight	50kg (2 hinges)
Fixed Light	
Max. Weight	250kg
SYSTEM FEATURES	
Single Colour	\checkmark
Dual Colour	\checkmark
Textured Finish	\checkmark
Anodised Finish	\checkmark
Multi-Point Locking	\checkmark
SIGHTLINES	
Frame to Vent	74mm
Vent to Mullion to Vent	111mm
Dummy Sash	74mm
GLAZING	
Glazing Options	Internal Bead
Glazing Thickness	24mm - 35mm

French Casement Floating Mullion

